

SUPERBOLT® SINGLE JACKBOLT TOOL

EFFORTLESS TIGHTENING AND UNTIGHTENING

Bridging the cost/performance gap between hand-tightening and the Superbolt Tool, this new product offers an effortless way to tighten and untighten our revolutionary multi-jackbolt tensioners (MJTs).

Advantages of the Superbolt Single Jackbolt Tool

- Effortless Operation: Tighten and untighten jackbolts with ease.
- Portability: Cordless design allows usage anywhere.
- Safety: Reduced manual work lowers the risk of injury.
- Precision: Ensure accurate tightening with precise torque application.

Quick Specs*

Torque Range	25-700 ftlbs. / 34 – 949 Nm
Weight (with battery)	7.3 – 8.22 lbs. / 3.32 – 3.74 kg
Square Drive	1/2 – 3/4 in.
RPM	4.1 - 11.6

*Depending on model - see other side for full specifications



0

SUPERBOLT 18V

SUPERBOLT

FULL SPECIFICATIONS



H = HEIGHT W = WIDTH L = LENGTH D = DIAMETER

MODEL NUMBER	н	W	L	D	SQUARE DRIVE	WEIGHT*	TORQUE		RPM
Imperial	in.				in.	lbs.	ft-lbs (min)	ft-lbs (max)	
.25	10.83	3.47	10.16	2.35	1/2	7.30	25	250	11.6
.7	10.83	3.47	11.13	2.45	3/4	8.22	70	700	4.1
Metric	mm.				in.	kg	Nm (min)	Nm (max)	
.25	275	88	258	60	1/2	3.32	34	339	11.6
.7	275	88	283	62	3/4	3.74	95	949	4.1

*with battery

IMPORTANT INFORMATION

The Single Jackbolt Tool is designed for MJT sizes starting at M64 (or 2-1/2"), as it is suited for jackbolts that are sized M16 (or 5/8") or larger in diameter. It becomes especially advantageous for MJT sizes over M100 (or 4"), which contain jackbolts that are sized M20 (or 3/4").

Reaction arm and jackbolt socket consideration are essential for proper Single Jackbolt Tool operation. A custom solution may be required.

For more help in proper selection or for more information, please contact your local Nord-Lock Group representative.

Nord-Lock, Inc. Tel +1 (412) 279-1149 www.nord-lock.com



© Copyright 2025 Nord-Lock Group. NORD-LOCK*, SUPERBOLT*, BOLTIGHT* and EXPANDER* SYSTEM are trademarks owned by different companies within the Nord-Lock Group. All other logos, trademarks, registered trademarks or service marks used herein are the property of the Nord-Lock Group. All rights reserved. 01058 TN V01